

CONTACT
0800 990 3258
enquiries@reagent.co.uk



ReAgent

SODIUM HYDROXIDE PEARL LRG MSDS

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	SODIUM HYDROXIDE PEARL LRG
CAS-No.	1310-73-2
EU INDEX NO.	011-002-00-6
EC No.	215-185-5
SUPPLIER	Reagent Chemical Services 18 Aston Fields Road Whitehouse Industrial Estate Runcorn Cheshire WA7 3DL T: 01928 716903 F: 01928 716425 E: info@reagent.co.uk
PRODUCT NO.	1561
APPLICATION	General chemical reagent

2 HAZARDS IDENTIFICATION

Causes severe burns.

CLASSIFICATION (67/548) -

3 COMPOSITION/INFORMATION ON INGREDIENTS

EU INDEX NO.	011-002-00-6
EC No.	215-185-5
CAS-No.	1310-73-2

4 FIRST-AID MEASURES

INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

INGESTION

Immediately rinse mouth and drink plenty of water. Get medical attention immediately!

SKIN CONTACT

Immediately remove contaminated clothing. Rinse the skin immediately with lots of water. Get medical attention immediately.

EYE CONTACT

May cause permanent damage if eye is not immediately irrigated. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention immediately. Continue to rinse.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

The product is non-combustible. Use fire-extinguishing media appropriate for surrounding materials.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Avoid dust formation. Transfer to a container for disposal. Wash contaminated area with water.

7 HANDLING AND STORAGE

SODIUM HYDROXIDE PEARL LRG**USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place.

STORAGE CLASS

Corrosive storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
SODIUM HYDROXIDE PEARL LRG	OES		2 mg/m ³	

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit (WEL) is not exceeded.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

HAND PROTECTION

Wear protective gloves. Rubber or plastic

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact. Provide eyewash station.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Solid		
COLOUR	White		
ODOUR	Odourless		
SOLUBILITY	Soluble in water.		
BOILING POINT (°C)	1390	MELTING POINT (°C)	318
RELATIVE DENSITY	2.12	pH-VALUE, DILUTED SOLUTION	14.5

10 STABILITY AND REACTIVITY**STABILITY**

Air and moisture sensitive.

MATERIALS TO AVOID

Aluminium, zinc, tin (formation of hydrogen). Acids. Organic cyanides (nitriles). Alkali earth metals. Inorganic cyanides. Magnesium. Organic nitro compounds. Phenols, cresols. Ammonium compounds (Formation of ammonia).

11 TOXICOLOGICAL INFORMATION**INHALATION**

Burns to mucous membranes.

INGESTION

Causes severe internal damage if swallowed.

SKIN CONTACT

Causes burns.

EYE CONTACT

Strongly corrosive. Causes severe burns. Immediate first aid is imperative.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.

13 DISPOSAL CONSIDERATIONS

SODIUM HYDROXIDE PEARL LRG

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

UK ROAD CLASS	8		
PROPER SHIPPING NAME	SODIUM HYDROXIDE, SOLID		
UN NO. ROAD	1823	UK ROAD PACK GR.	II
ADR CLASS NO.	8	ADR CLASS	Class 8: Corrosive substances.
ADR PACK GROUP	II	ADR LABEL NO.	8
HAZCHEM CODE	2X	CEFIC TEC(R) NO.	80GC6-II+III
RID CLASS NO.	8	RID PACK GROUP	II
UN NO. SEA	1823	IMDG CLASS	8
IMDG PAGE NO.	8	IMDG PACK GR.	II
EMS	F-A, S-B	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1823
AIR CLASS	8	AIR PACK GR.	II

15 REGULATORY INFORMATION

LABELLING



Corrosive

RISK PHRASES

R35 Causes severe burns.

SAFETY PHRASES

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

S37/39 Wear suitable gloves and eye/face protection.

S1/2 Keep locked up and out of the reach of children.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. COSHH essentials: Easy steps to control chemicals. Control of Substances Hazardous to Health Regulations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

NATIONAL REGULATIONS

Control of Substances Hazardous to Health Regulations 2002 (as amended)

16 OTHER INFORMATION

GENERAL INFORMATION

Under REACH Material Safety Datasheets (MSDS) are referred to as Safety Datasheets (SDS).

REVISION COMMENTS

General rewrite

REVISION DATE May 2004

REV. NO./REPL. SDS GENERATED Supercedes issue December 2001

SDS NO. 20465

SODIUM HYDROXIDE PEARL LRG