

CONTACT  
0800 990 3258  
[enquiries@reagent.co.uk](mailto:enquiries@reagent.co.uk)



# ReAgent

## SAFETY DATA SHEET SODIUM HYDROXIDE 47% W/W

According to Regulation (EC) No 1907/2006

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME SODIUM HYDROXIDE 47% W/W  
 PRODUCT NO. 1287  
 APPLICATION General chemical reagent  
 SUPPLIER Reagent Chemical Services  
 18 Aston Fields Road  
 Whitehouse Industrial Estate  
 Runcorn  
 Cheshire WA7 3DL  
 T: 01928 716903  
 F: 01928 716425  
 E: [info@reagent.co.uk](mailto:info@reagent.co.uk)  
 EMERGENCY TELEPHONE Emergency Telephone : +44 (0) 1928 716903 Between 08.30 - 17.00

### 2 HAZARDS IDENTIFICATION

Causes severe burns.

CLASSIFICATION C;R35.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
SODIUM HYDROXIDE	215-185-5	1310-73-2	30-60%	C;R35

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

#### INGESTION

Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Get medical attention immediately!

#### SKIN CONTACT

Immediately remove contaminated clothing and wash before re-use. Rinse the skin immediately with lots of water. Get medical attention immediately.

#### EYE CONTACT

May cause permanent damage if eye is not immediately irrigated. Promptly wash eyes with plenty of water or eye wash solution while lifting the eyelids. If possible remove any contact lenses and continue to wash. Get medical attention immediately.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

The product is non-combustible. Use fire-extinguishing media appropriate for surrounding materials.

#### SPECIFIC HAZARDS

Corrosive liquid.

#### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

### 6 ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

**SODIUM HYDROXIDE 47% W/W****SPILL CLEAN UP METHODS**

Small Spillages Absorb with sand or other inert absorbent. Large Spillages Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Wash thoroughly after dealing with a spillage.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Store in tightly closed original container in a dry and cool place.

**STORAGE CLASS**

Corrosive storage.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
SODIUM HYDROXIDE	OES		2 mg/m3	

**ENGINEERING MEASURES**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

**RESPIRATORY EQUIPMENT**

In case of inadequate ventilation use suitable respirator.

**HAND PROTECTION**

Use full-length gloves. Rubber or plastic Be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Wear goggles/face shield.

**OTHER PROTECTION**

Wear suitable protective clothing as protection against splashing or contamination. Provide eyewash station and safety shower.

**HYGIENE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes wet or contaminated. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Liquid
COLOUR	Colourless
ODOUR	Odourless
SOLUBILITY	Miscible with water.
pH-VALUE, CONC. SOLUTION	14

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Air sensitive.

**MATERIALS TO AVOID**

Light metals (Formation of hydrogen). Ammonium compounds (Formation of ammonia). Acids.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

Burns to mucous membranes.

**INGESTION**

Corrosive. Even small amounts may cause serious damage.

**SODIUM HYDROXIDE 47% W/W****SKIN CONTACT**

Causes severe burns.

**EYE CONTACT**

Strongly corrosive. Causes severe burns and serious eye damage. Immediate first aid is imperative.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

UK ROAD CLASS	8		
PROPER SHIPPING NAME	SODIUM HYDROXIDE SOLUTION		
UN NO. ROAD	1824	UK ROAD PACK GR.	II
ADR CLASS NO.	8	ADR CLASS	Class 8: Corrosive substances.
ADR PACK GROUP	II	ADR LABEL NO.	8
HAZCHEM CODE	2R	CEFIC TEC(R) NO.	80GC5-II+III
RID CLASS NO.	8	RID PACK GROUP	II
UN NO. SEA	1824	IMDG CLASS	8
IMDG PAGE NO.	8	IMDG PACK GR.	II
EMS	F-A, S-B	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1824
AIR CLASS	8	AIR PACK GR.	II

**15 REGULATORY INFORMATION****LABELLING**

Corrosive

**CONTAINS**

SODIUM HYDROXIDE

**RISK PHRASES**

R35 Causes severe burns.

**SAFETY PHRASES**

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

S24/25 Avoid contact with skin and eyes.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S60 This material and its container must be disposed of as hazardous waste.

**STATUTORY INSTRUMENTS**

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

## SODIUM HYDROXIDE 47% W/W

### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. COSHH essentials: Easy steps to control chemicals. Control of Substances Hazardous to Health Regulations.

### GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

### NATIONAL REGULATIONS

Control of Substances Hazardous to Health Regulations 2002 (as amended)

## 16 OTHER INFORMATION

### REVISION COMMENTS

Change to section 1

REVISION DATE 25/09/2008

REV. NO./REPL. SDS GENERATED 1

SDS NO. 10021

### RISK PHRASES IN FULL

R35 Causes severe burns.